



AERODYNAMIC SKIRTS EDGE & ez-EDGE

Cutting Your Costs, Fueling Your Profits

TRANSTEX is the leader in the development and manufacturing of aerodynamic solutions for commercial vehicle applications. Made from glass-reinforced thermoplastic composite, EDGE and ez-EDGE aerodynamic skirts are the industry leaders in performance, reliability and value. Highly durable and flexible, EDGE and ez-EDGE solutions are manufactured to be as tough as your trailer. Both products are available for a variety of trailer applications and deliver up to 7.3% fuel savings. EDGE and ez-EDGE aerodynamic skirts are EPA SmartWay® Verified Advanced Category, C.A.R.B. Compliant and EPA GHG Phase 2 BIN 3 Pre-approved.

THE TRANSTEX ADVANTAGE

- Designed for quick and easy installation
- Low maintenance for reduced cost of ownership
- Available for installation at OEMs and local dealers
- Highly durable and flexible materials can withstand steep angled docks
- UV protection rating of 15,000 hours



THE BLUE BRACKET: BENDS BUT NEVER BREAKS

TRANSTEX has designed and developed the Blue Bracket; a revolutionary patented product that bends but never breaks. Its concave design provides flexibility and durability without permanent deformation ensuring that you won't waste time adjusting, repairing or replacing brackets. The Blue Bracket is angled to withstand a bigger load before deflecting, keeping your panels straight and reducing vibrations for optimized aerodynamics.

THE BRACKET ADVANTAGE







- Pre-assembled hardware
- Engineered material with a nylon base
- Designed to be robust and flexible
- Hot-dipped galvanized hardware and stainless steel bolts for corrosion resistance

Part Number	T-FLEX
Weight	2.1 lbs*

**Includes Hardware*



EDGE FAMILY OF SOLUTIONS

Part Number	 E-1332T	 E-1830T	 EZ-1932T	 E-1932T	 E-2330T	 E-2332T
Application	Pup Trailers	48 ft. Dry Vans & Reefers	53 ft. Dry Vans & Reefers	53 ft. Dry Vans & Reefers Intermodal, Non-Recessed	53 ft. Dry Vans & Reefers	53 ft. Intermodal Recessed 8 in. Inboard
Intermodal	✗	✗	✗	✓	✗	✓
Length	13 ft.	18 ft.	19 ft.	19 ft.	23 ft.	23 ft.
Height	32 in.	30 in.	32 in.	32 in.	30 in.	32 in.
Weight	101 lbs*	124 lbs*	140 lbs*	137 lbs*	157 lbs*	166 lbs*
Category	✗	✗	Advanced Trailer Skirt (more than 5%**)	Advanced Trailer Skirt (more than 5%**)	Advanced Trailer Skirt (more than 5%**)	Advanced Trailer Skirt (more than 5%**)
SmartWay Verified	✗	✗	✓	✓	✓	✓
C.A.R.B Compliant	✗	✗	✓	✓	✓	✓
Installation Time (Two Trained Technicians)	25 min.	30 min.	30 min.	30 min.	30 min.	30 min.
Colors	<input type="radio"/> <input type="radio"/> <input type="radio"/>	<input type="radio"/> <input type="radio"/> <input type="radio"/>	<input type="radio"/> <input type="radio"/>	<input type="radio"/> <input type="radio"/> <input type="radio"/>	<input type="radio"/> <input type="radio"/> <input type="radio"/>	<input type="radio"/> <input type="radio"/> <input type="radio"/>

** Includes Brackets and Hardware*

*** Wind Tunnel and CFD Tested*